



- ROAD SERVICE REQUIREMENTS.**
1. VISIBILITY SPLAYS TO BE 2.4M X 32M
 2. AREAS BETWEEN SIGHT LINES AND ROAD EDGE TO BE LABELLED TO GRASS VERGE LEVEL, AND TO BE NON HIGHER THAN 250MM
 3. WALLS, HEDGES, POLES ETC TO BE REPT BEHIND SIGHT LINES.
 4. MINIMUM TURN IN RADIUS 5M.
 5. MINIMUM WIDTH OF ACCESS 3.2M
 6. THE GRADIENT OF THE ENTRANCE FOR A DISTANCE OF 5M FROM THE ENTRANCE GATES SHALL BE SHIELD AT LEAST 5M FROM THE EDGE OF THE CARRIAGEWAY AND SHALL BE HUNG SO THAT THEY DO NOT DAMAGE TO BE PROVIDED TO PREVENT WATER FROM THE CARRIAGEWAY FLOWING ONTO THE CARRIAGEWAY AND NO VISIBILITY SPLAYS AND PARKING SPACE OFF THE CARRIAGEWAY HAS BEEN PROVIDED.

- PLANTING**
- PROVIDE NEW HEDGEROWS TO BOUNDARIES AS SHOWN:
 CRATAEGUS MONOZYMA
 FAGUS HETROPHYLIA
 LIGUSTRUM OVALIFOLIUM
- SUGGESTED TREE SPECIES TO HEDGEROW TO INCLUDE:
 FRAXINUS EXCORSIS
 BETULA EXCORSIS
 SORBUS AUCUPARIA

revisions	date	description
2		

...david haire
 architectural design

416 avenue rd Lurgan B16C Crd
 t: 36 344323 e: 07900 276696
 email: info@davidhaire.co.uk

Project: **title**
 Proposed building and design package 1:20m
 500m W of 1st Blackskull
 for existing developments

1:500 | scale
 sep 08 | date
 06-11-14-01 | dwg