



FIRE CERTIFICATE FC 003 02
DRAWING No. 1 of 6
AMENDED 12th MAY 2005

AMENDED 12th MAY 2005

AMENDED 12th MAY 2005

[illegible]

CONSTRUCTION SHOWN IN BOLD LINES IS ACCEPTED AS PROVIDING A MINIMUM OF 1/2 HOUR FIRE RESISTANCE UNLESS OTHERWISE INDICATED. DOORS SHOWN IN BOLD LINES ARE ACCEPTED AS PROVIDING A MINIMUM OF 1 HOUR FIRE RESISTANCE. THEY MUST BE EFFECTIVELY MAINTAINED AS SELF-CLOSING, OR AS IN THE CASE C STORE DOORS, NEPT LOOKED SHUT WHEN NOT IN USE. THE APPROPRIATE NOTICE IS DISPLAYED ON ALL FIRE DOORS.

[illegible][illegible]

| | | | | |
|------|-----------------------|--|-----------------------|---------------------------|
| | WP | Weaver's production | — | Five minutes construction |
| | N | For meeting doors 30 minutes minimum | 60 | Five minutes minimum |
| | N | For meeting doors 60 minutes minimum | 60 | Five minutes construction |
| | N | For meeting doors 90 minutes minimum | 60 | Five minutes minimum |
| | N | For meeting doors 120 minutes minimum | f | Internal clarity |
| VE | Vertical ladder | HRL | Horizontal | |
| VP | Urban panel | QRL | Quadrant | |
| PPL | Public space exhibits | PB | Push bar to open | |
| EOD | Emergency devices | O | Outward opening | |
| SC | Self closing device | D | Double acting | |
| SC/S | Automatic releases | PSO | Fire resisting gasket | |
| FFT | Free fire treatments | FR | Fire resisting | |